

## **19155 N120 DSLR Gear Set for Laowa 24mm f/14 2x Macro Probe**

Instruction Manual

### **FOREWORD**

Thank you for your purchase of a NAUTICAM product.

At NAUTICAM, we pride ourselves in the ability to recognize the requirements of professional as well as amateur underwater photographers and fulfill them through the innovative designs of our products. We strive to achieve a high level of user-friendliness by allowing stress-free installation and easy operation of all important functions of the camera.

Please read this manual carefully before using the product, this will maximize its performance as well as its lifetime.

### **WARRANTY**

All NAUTICAM Products are warranted against any material and manufacturing defects for two years from the date of purchase for consumer use. This warranty only applies to products purchased from authorized NAUTICAM dealers and does not extend beyond the original retail purchaser.

To return your product for service, please contact your regional authorized service centre(s). Please note that this warranty only applies when the product is purchased in the territory where the service centre is located.

NAUTICAM does not hold responsibility for damage, of any nature, to any equipment used with and/or placed within our products.

NAUTICAM accepts no liability for any loss of captured images or the inability to capture images even if it is due to the malfunctioning of our products.

Unauthorized modifications and/or repairs of our products will automatically invalidate the warranty.

### **IDENTIFICATION OF THE PARTS**



**\*\*19155 N120 DSLR Gear Set for Laowa 24mm f/14 2x Macro Probe is designed for both Laowa 24mm cine version and standard version Lenses to use with N120 DSRL housing.**

It includes a set of Iris and Focus gear (Iris gear is controlled by #21271 Extension ring 70 with focus knob, and focus gear is controlled by DSLR housing zoom/focus knob), a set of Iris and Focus C-Ring for cine version lens and another C-Ring set for standard version, and two spacers as shown above.

Please use corresponding C-rings

\*\*The depth rating of this lens is 30 meter.

### **MOUNTING THE GEARS ON A LENS**



1. Insert the Focus C-ring and Iris C-ring in this order as shown and place them over the lens



2. To use with Nikon F mount lens, place the Big spacer on the focus C-ring and Small spacer on the Iris C-ring  
Canon EF mount lens needs to use the spacers.



3. Insert the focus gear on the focus C-ring, then gently push down the gear towards the bottom until it cannot go any further.



4. Insert the Iris gear on the Iris C-ring, then gently push down the gear towards the bottom until it cannot go any further as focus gear  
To remove the gear set, reverse the above steps.

The tightness between the gear set and the lens can be adjusted by removing or adding rubber grips on either sides of the plastic C-ring. Spare rubber grips are included in the package.